

DHI-LM24-B200

23.8" FHD Monitor



Technical Specification

Model

| | |
|-------|---------------|
| Model | DHI-LM24-B200 |
|-------|---------------|

Display

| | |
|----------------------|---------------------|
| Screen Size | 23.8" |
| Aspect Ratio | 16:9 |
| Resolution | 1920×1080 (FHD) |
| Backlight | LED |
| Brightness/Luminance | 250 cd/㎡ |
| Contrast | 4000:1 |
| Display Color | 16.7M(8bit) |
| Viewing Angle(H/V) | 178°(H)/178°(V) |
| Response time(typ.) | 6.5ms |
| Refresh Rate | Max.75Hz , Typ.60Hz |

Signals

| | |
|--------|---------------|
| Input | VGA×1, HDMI×1 |
| Output | Audio Out x1 |

General

| | |
|--------------|----------------------|
| Power Supply | AC100~240V, 50/60 Hz |
|--------------|----------------------|

Features :

- Light and cost-effective plastic housing;
- Ultra-narrow bezel, elegant appearance, metal base;
- 178°H/178°V extra-wide viewing angle for overall viewing performance;
- High fidelity digital processing for a brilliant and vivid video;
- Support multiple signal inputs including HDMI and VGA;
- Low energy consumption, long service life;
- Anti-blue light design, eye-protective.



| | | |
|------------------------------------|----------------------------------|-----------------------|
| Consumption (Standard) | 25W | |
| Consumption (Standby) | ≤0.5W | |
| Type | Internal | |
| Net Weight | 3kg (6.6lb) | |
| Gross Weight | 4kg (8.8lb) | |
| Bezel Width | 3.8mm(U), 3.7mm(R/L), 11mm(B) | |
| Wall Mount | 75×75mm (3.0"×3.0") | |
| Dimension without standard (W×H×D) | 541×317×42mm (21.3"×12.5"×1.7") | |
| Package(W×H×D) | 613×441×112mm (24.1"×17.4"×4.4") | |
| Work Environment | Temperature | 0 C~40 C (32°F~104°F) |
| | Humidity | 10%~85% |

Accessory

| | |
|----------|-------------------------------|
| Standard | HDMI cable, power cable, base |
| Optional | Gas spring desk bracket |

Certifications

| | |
|----------------|--------|
| Certifications | CE/FCC |
|----------------|--------|

Dimensions(mm)

